



Tandem Axle Specifications	6' X 10' & 12'	7' X 10', 12', 14', 16' & 18'	8.5' X 14', 16', 18', 20', 22' & 24'
Exterior Side Metal	0.024 Gauge Aluminum	0.024 Gauge Aluminum	0.024 Gauge Aluminum
Roof Metal	Galvalume	Galvalume	One Piece Aluminum
Cross Members	16" O.C.	16" O.C.	16" O.C.
Roof Bows	24" O.C.	24" O.C.	24" O.C.
Side Wall Studs	16" O.C.	16" O.C.	16" O.C.
Floor Boards	¾" Plywood	¾" Plywood	¾" Plywood
Wall Boards	3/8" Plywood	3/8" Plywood	3/8" Plywood
Ramp Door	Opt.	Opt.	Opt.
Rear Door	Opt. - Double w/ bar lock	Opt. - Double w/ bar lock	Opt. - Double w/ bar lock
Interior Height	6'3"	6'3"	6'6"
Jack	2,000 lb.	2,000 lb.	2,000 lb.
Side Wall Vents	Opt.	Opt.	Opt.
Exterior Fastening	Color Matching Screws	Color Matching Screws	Color Matching Screws
Stone Guard	24"	24"	24"
Coupler	2 5/16"	2 5/16"	2 5/16"
Frame	All Tubular Perimeter	All Tubular Perimeter	All Tubular Perimeter
Nose	Soft-Vee	Soft-Vee	Soft-Vee
Roof Vent	Non-powered	Non-powered	Non-powered
Axle	3,500 lb. Brakes Spring	3,500 lb. Brakes Spring	3,500 lb. Brakes Spring
GVWR	7,000 lb.	7,000 lb.	7,000 lb.
GAWR	3,500 lb.	3,500 lb.	3,500 lb.
Payload	4,170 lb. - 5,580 lb.	4,330 lb. - 5,010 lb.	3,200 lb. - 4,160 lb.
Shipping Weight	1,620 lb. - 1,820 lb.	1,890 lb. - 2,510 lb.	2,740 lb. - 3,600 lb.
Wheels	White/Silver Mod	White/Silver Mod	White/Silver Mod
Tires	ST205 15" Radial	ST205 15" Radial	ST205 15" Radial
Hubs	EZ LUBE Drop Hub	EZ LUBE Drop Hub	EZ LUBE Drop Hub
Electrical Plug	7 – Way Bargman	7 – Way Bargman	7 – Way Bargman
Interior Light	12 Volt LED Dome	12 Volt LED Dome	12 Volt LED Dome
Tail Lights	LED	LED	LED
Fenders/ Corners	Anodized or ATP	Anodized or ATP	Anodized or ATP
Side Door w/ Flush Lock	32" X 68"	32" X 68"	32" X 72"